




ELKE 4408 V FM 8 05

Industrial Connectors: Circular connectors E-series M8: with screw locking: Appliance socket and appliance connector for front panel mounting

Delivery informations	
Availability	available
Document created at	24.03.2009
Product description	
Description	Front-mounting appliance socket with stranded wire, screw locking, M8 x 0.5 mounting thread, metal casing, O-ring included
Type	ELKE 4408 V FM 8 05
Order No.	933 382-100
Type of contact	female
Number of contacts	4
Cable material	PVC
Cable length	0.5 m
Conductor size	0.25 mm ²
Standard	IEC 61076-2-101 (Ed. 1)/ IEC 60947-5-2
Housing Color	metallic
Drawing	



Technical data	
Wire stranding	14 x 0.15 mm
Rated voltage	AC/DC 30 V
Rated current	3 A
Material	

Contact material	Cu Zn
Contact surface material	Au
Contact bearer material	PA black
Housing material	Cu Zn/Ni
O-Ring	NBR
Environmental conditions	
Protection class (IEC 60529)	IP 68
Pollution severity	3
Temperature range	-25 °C to +90 °C
Inflammability class	
Contact bearer	94 V-2
Approvals	
UL	UL
Packing unit	
Packaging unit	100 pieces
Scope of delivery and accessories	
Accessories to order separately	fastening nut ELST M M8, order no. 734 032-001