



N° of circuits: 9x signal ; 3x power (all contacts gold-gold)  
 Voltage max: 48 VDC signal ; 230 VAC power  
 Current max. p. Ring: 2 A signal ; 1x 3 A and 2x 10 A power  
 R.P.M. max: 250  
 Protection Class: IP 54  
 Lead wires: LiY12CY 10x0,14mm<sup>2</sup> signal ; LiYY 3x1,0mm<sup>2</sup> power  
 Temperature Range: 0°C - 60°C

Oberflächenzustand:		Freimaßtoleranzen DIN 7168-m		Alu / PCGF30	
		Formtoleranzen DIN 7184		Mat.-N°:	
h)		Datum	Name	<b>Slip Ring Capsule</b> <b>SC080-09/03-EXX</b>	
g)		Bearb. 10.01.05	Piederstorfer		
f)		Gepr. 10.01.05	Angerpointner		
e)		Norm			
d)		Kom.-N°:			
c)		<b>LTN</b> <b>LTN Servotechnik GmbH</b>		Zeichnungs-N°: SC080-09/03-EXX	
b)				EDV-N°:	
a)					
Zust.	Änderung	Datum	Name	Datei: SC080-09-03-EXX DXF:	Maßstab <b>1:1</b> O-Format <b>A3q</b>
				10.01.05	