# **Slip Rings With Through-Bores**

# SRA-73683

# 1/2 inch through-bore miniature slip ring capsule

## **Description**

A slip ring capsule can be used in any electromechanical system that requires unrestrained, intermittent or continuous rotation while transferring power and / or data. A slip ring is also called a rotary electrical joint, collector, commutator or swivel. A slip ring can improve system performance by simplifying operations and eliminating damage prone wires.

The SRA-73686 provides an economical, readily available solution when a compact through-bore configuration is required. This unit provides a 1/2 inch through-bore for shaft mounting, and a compact 1.375 inch outside diameter and a very short overall length for minimal space applications. The SRA-73683 provides 2 amp circuits in 6, 12, 18 and 24 ring configurations.

#### **Features**

- 1/2 inch through-bore
- Compact 1.375 inch outside diameter
- · Speeds up to 120 rpm continuous
- · Continuous rotation of power and / or data signals

#### **Benefits**

- · Transfers power, as well as analog and digital signals
- · Compatible with data bus protocols
- · Compact packaging



## **Typical Applications**

- Precision rotary equipment
- · Semiconductor handling systems
- Robotics
- · Camera systems

15

# **Slip Rings With Through-Bores**

Specifications		Options
Operating Speed	120 rpm* continuous	Flange on stator housing
Number of Circuits	6, 12, 18, 24	
Lead Length	4 inch each end	
Lead Size / Type	#26 AWG, Teflon® insulated, stranded	
Voltage	210 VAC	
Operating Temp.	-40°C to +80°C	
Contact Material	Gold	
Current Rating	2 A, per ring, max.	
Dielectric Strength	500 VRMS, all combinations	
Insulation Resistance	1000 megohms min. @ 500 VDC	
Electrical Noise	10 milliohm max. @ max. speed	

<sup>\*</sup>Please note that the operational life of the unit is dependent upon rotational speed, environment and temperature.

Part Number	Length "A"	Ring Qty.
SRA-73683 - 6	.98 inch (24,89 mm)	6
SRA-73683 - 12	1.12 inch (28,45 mm)	12
SRA-73683 - 18	1.42 inch (36,07 mm)	18
SRA-73683 - 24	1.72 inch (43,69 mm)	24

Wire Color Code					
Ring #	Color	Ring #	Color		
1	BLK	13	WHT-RED		
2	BRN	14	WHT-ORN		
3	RED	15	WHT-YEL		
4	ORN	16	WHT-GRN		
5	YEL	17	WHT-BLU		
6	GRN	18	WHT-VIO		
7	BLU	19	WHT-GRY		
8	VIO	20	WHT-BLK-BRN		
9	GRY	21	WHT-BLK-RED		
10	WHT	22	WHT-BLK-ORN		
11	WHT-BLK	23	WHT-BLK-YEL		
12	WHT-BRN	24	WHT-BLK-GRN		

## **SRA-73683 Dimensions**

