



ProcessSensor

## Selection Guide

Main features	BeanDevice® AN-420	BeanDevice® AN-V	BeanDevice® AN-mV	BeanDevice® AN-420 Xtender	BeanDevice® AN-V Xtender	BeanDevice® AN-mV Xtender
Measurement range	4-20mA	±5V or ±10V	±20mV	4-20mA	±5V or ±10V	±20mV
External sensor power supply	4.5 to 20 volts, configurable from the <i>BeanScope® software</i>					
Measurement accuracy (% on full scale)	< 0,1% when plugged on external power supply < 0,08% when operating on battery power			< 0,08%		
Number of channels	2 or 4 channels			4 channels		
Maximum wireless Range (L.O.S.)	1 km					
Maximum sampling rate per channel (SPS—sample per second)	400 SPS			N.A.		
Data Logger Size	1 million data points					
Internal primary Cell/Battery	<u>Rechargeable battery</u> : Lithium-polymer, 950 mAh			<u>Primary cell</u> : Lithium-thionyl chloride, 6.5Ah		
Operating temperature	-20°C to +65°C			-40°C to +85°C		
Casing	Aluminum, Watertight IP65 casing dimensions (without antenna) L x l x h : 146.05 mm x 65.5mm x 33.5 mm			Aluminum, Watertight IP65 casing dimensions (without antenna) L x l x h : 149.1 mm x 77mm x 60.5 mm		


  
[sales@beanair.com](mailto:sales@beanair.com)  
 Tel.: +49 30 98366680  
[www.beanair.com](http://www.beanair.com)  
 Visit our blog: [www.industrial-wsn.com](http://www.industrial-wsn.com)



[Watch our featured videos on Youtube](#)



*BeanDevice® AN-420 Main presentation Video*



*BeanDevice® AN-420 configuration Video*



*BeanDevice® AN-420 Wireless Range Video*

