

# Protection components

## VARIO switch disconnectors for high performance applications

### Complete units


- 3-pole rotary switch disconnectors, 12 to 175 A
- Marking on operator  $\text{O} \downarrow$ .
- Padlockable operating handle (padlocks not supplied).
- Degree of protection IP 65.



VBD 0



VBF 4



VVE 1

#### Main switch disconnectors for door mounting

Handle	Front plate mm	Fixing	Rating A	Reference	Weight kg
Black, padlockable with up to 3 padlocks (Ø 4 to Ø 8)	Black 60 x 60	Ø 22.5	12	VBD 02	0.215
			20	VBD 01	0.215
			25	VBD 0	0.215
			32	VBD 1	0.215
			40	VBD 2	0.215
4 screws			12	VBF 02	0.250
			20	VBF 01	0.250
			25	VBF 0	0.250
			32	VBF 1	0.250
			40	VBF 2	0.250
			63	VBF 3	0.560
			80	VBF 4	0.560
			Red, long, padlockable with up to 3 padlocks (Ø 4 to Ø 8)	Black 90 x 90	4 screws
175	VBF 6	1.200			

#### Main and Emergency stop switch disconnectors

##### For mounting in an enclosure or for modular distribution boards

Handle	Front plate mm	Rating A	Reference	Weight kg
Red, padlockable with 1 padlock (Ø 4 to Ø 6)	Yellow 45 x 45	25	VVE 0	0.250
		32	VVE 1	0.250
		40	VVE 2	0.250
		63	VVE 3	0.530
		80	VVE 4	0.530

#### Main switch disconnectors

##### For mounting in an enclosure or for modular distribution boards

Handle	Front plate mm	Rating A	Reference	Weight kg
Black, not padlockable	Black 45 x 45	25	VVD 0	0.250
		32	VVD 1	0.250
		40	VVD 2	0.250
		63	VVD 3	0.560
		80	VVD 4	0.560